

W-Series 100G Solid Mount Washers

Wascomat W-Series washers combine world-class reliability with innovative features and programmability. Featuring 100 G-force extraction and Compass Pro, Wascomat washers increase productivity, lower utility costs, and eliminate laundry headaches. Wascomat makes it easy and affordable to upgrade your laundry!



Wascomat 100 G-Force Washers with Compass Pro continue a long tradition of excellence in technology, design, and quality:

- Low water consumption
- Single phase simplicity in 120 or 220 volt
- Inverter driven motor for smooth and quiet operation, and higher efficiency
- Robust door handle — durable in any environment
- Door unlocks immediately at the end of final cycle — no delays
- Unique 4-compartment supply dispenser lets you conveniently load all laundry supplies before starting the wash
- Provisions to connect 5 liquid supplies
- Riveted unibody steel construction eliminates welds for strength and durability
- Interchangeable parts from one machine size to another

Features and Benefits

Wascomat Compass Pro provides the ultimate in flexibility and control over your laundry operations:

- Customize wash programs to lower costs and increase productivity
- Display wash program information in two languages simultaneously
- Library of factory supplied, built-in programs with room for more
- Reduce operator error by displaying only the programs you use
- Built-in diagnostics and detailed statistics
- Real-time clock for delayed start

Environmentally Responsible

With more than a century of experience behind every machine, Wascomat's state-of-the-art products are engineered for quality, energy savings, and water efficiency. When you buy Wascomat, you are truly investing in the future of your business.

Most sizes available in 220 or 120 volt, single phase

Now it's easy to replace old, inefficient top loaders with new Wascomat front loaders!

Compass Pro Microprocessor

With Compass Pro you choose the programs that best suit your needs. Modify standard wash programs to find the perfect balance between low water and energy consumption — or create your own programs to meet the specific needs of your facility.

Compass Pro puts you in complete control of your on-premises laundry operations. One knob does it all!

| Wascomat "W" Series, 100G Washers | W720 | | W725 | | W730 | | W745 | | W762 | | W777 | |
|---|--------------------|-------------|--------------------|-------------|--------------------|-------------|--------------------|-------------|--------------------|-------------|--------------------|-------------|
| Capacity (lb/kg) | 20 | 9 | 25 | 11 | 30 | 14 | 45 | 20 | 62 | 28 | 77 | 35 |
| Width (in/mm) | 26 | 660 | 28 3/8 | 720 | 28 3/8 | 720 | 29 1/2 | 750 | 32 11/16 | 830 | 35 13/16 | 910 |
| Depth (overall) (in/mm) | 28 7/16 | 722 | 27 7/16 | 697 | 31 | 787 | 36 | 914 | 40 1/2 | 1029 | 43 7/8 | 1114 |
| Height (in/mm) | 44 5/8 | 1133 | 47 15/16 | 1217 | 47 7/8 | 1216 | 52 15/16 | 1345 | 56 1/8 | 1426 | 57 11/16 | 1465 |
| Height to bottom of door (in/mm) | 14 | 355 | 14 3/8 | 365 | 14 3/8 | 365 | 17 1/8 | 435 | 18 1/2 | 470 | 19 11/16 | 500 |
| Door opening diameter (in/mm) | 12 1/4 | 310 | 14 3/8 | 365 | 14 3/8 | 365 | 15 9/16 | 395 | 17 1/8 | 435 | 17 1/8 | 435 |
| Cylinder volume (ft ³ /l) | 3 | 85 | 3.7 | 105 | 4.6 | 130 | 6.4 | 180 | 8.8 | 250 | 11.7 | 330 |
| Drain outlet diameter (in/mm) | 3 | 75 | 3 | 75 | 3 | 75 | 3 | 75 | 3 | 75 | 3 | 75 |
| Height to centerline of drain (in/mm) | 4 1/16 | 103 | 4 1/16 | 103 | 4 1/16 | 103 | 4 1/16 | 103 | 4 1/16 | 103 | 4 1/16 | 103 |
| Extract (rpm/G-Force) | 587/100 | | 548/100 | | 548/100 | | 525/100 | | 497/100 | | 474/100 | |
| Dynamic floor load (lb/kN) | 382 +/- 697 | 1.7 +/- 3.1 | 427 +/- 562 | 1.9 +/- 2.5 | 540 +/- 697 | 2.4 +/- 3.1 | 652 +/- 877 | 2.9 +/- 3.9 | 854 +/- 1102 | 3.8 +/- 4.9 | 1034 +/- 1259 | 4.6 +/- 5.6 |
| Dynamic frequency (Hz) | 9.3 | | 9.1 | | 9.1 | | 8.8 | | 8.3 | | 7.9 | |
| Noise level (dBA) in extraction | <70 | | <70 | | <70 | | <72 | | <71 | | <74 | |
| Crated width - (in/mm) | 27 3/16 | 690 | 29 1/2 | 750 | 29 1/2 | 750 | 30 11/16 | 780 | 33 7/8 | 860 | 37 | 940 |
| Crated depth - (in/mm) | 32 11/16 | 830 | 35 1/16 | 890 | 37 3/8 | 950 | 39 3/16 | 995 | 43 11/16 | 1110 | 47 1/16 | 1195 |
| Crated height - (in/mm) | 48 | 1219 | 53 1/8 | 1350 | 53 1/8 | 1350 | 56 7/16 | 1434 | 61 1/4 | 1556 | 62 7/16 | 1586 |
| Crated weight (lb/kg) | 276 | 126 | 364 | 166 | 370 | 169 | 522 | 238 | 615 | 280 | 717 | 326 |
| Electrical Requirements (standard) | | | | | | | | | | | | |
| Voltage/frequency/phase | 208-240/60/1 or 3- | | 208-240/60/1 or 3- | | 208-240/60/1 or 3- | | 208-240/60/1 or 3- | | 208-240/60/1 or 3- | | 208-240/60/1 or 3- | |
| Power (kW) / Full-load current (A) / Ckt breaker (A) | 0.5 / 2.4 / 15 | | 0.7 / 3.4 / 15 | | 0.8 / 3.9 / 15 | | 0.9 / 4.3 / 15 | | 1.1 / 5.3 / 15 | | 1.2 / 5.8 / 15 | |
| Voltage/frequency/phase | 120/60/1 | | 120/60/1 | | 120/60/1 | | 120/60/1 | | 120/60/1 | | 120/60/1 | |
| Power (kW) / Full-load current (A) / Ckt breaker (A) | 0.6 / 5.0 / 15 | | 0.8 / 5.8 / 15 | | 0.9 / 7.5 / 15 | | 1.0 / 8.3 / 15 | | 1.2 / 10.0 / 15 | | 1.3 / 10.8 / 15 | |
| Water Information | | | | | | | | | | | | |
| Inlet fittings (* = 3 inlets) | 3/4 | DN20 | 3/4 | DN20 | 3/4 | DN20 | 3/4* | DN20* | 3/4* | DN20* | 3/4* | DN20* |
| Flow (gpm/lpm @ 45 psi) (each inlet) | 5 | 20 | 5 | 20 | 5 | 20 | 5 | 20 | 16 | 60 | 16 | 60 |
| Recommended water pressure (psi/kPa) | 30-90 | 200-600 | 30-90 | 200-600 | 30-90 | 200-600 | 30-90 | 200-600 | 30-90 | 200-600 | 30-90 | 200-600 |
| Approx Water usage (gal / liters @ full load) | 12.9 | 49 | 16.3 | 61.7 | 20.9 | 79 | 30.4 | 115 | 42.8 | 162 | 53.6 | 203 |
| Modified Energy Factor | n/a | | | | | | | | | | | |
| Water Factor (Gal per cycle/drum volume) | 4.3 | | 4.4 | | 4.5 | | 4.8 | | 4.8 | | 4.6 | |
| Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact Laundrylux for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information. | | | | | | | | | | | | |

Call today for information on the full line of Wascomat Commercial Laundry Equipment and low-cost financing.



Laundrylux

800.645.2204 • laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338

Sales & Administration: 516-371-4400 • F 516-371-4204 • sales@laundrylux.com

Parts: 516-371-2000 • F 516-371-4029 • parts@laundrylux.com

Tech Support: 516-371-0700 • F 516-371-4029 • service@laundrylux.com

En Mexico: Llame gratis a este numero 001-800-010-1010