

## Extra Spin "X" 220-300G Washer W5350X - 77 lb

## **Features and benefits**

- Compass Pro® microprocessor offers:
  - Large display and one control knob for easy program selection
  - Language selection
  - Quick selection and option buttons for the most frequently used wash programs and options
- AWS Automatic Water Savings:
  - Save up to 30% on water with AWS automatically. With every wash cycle, AWS determines the actual weight of the load and adds precisely the right amount of water, significantly reducing water consumption and energy costs
- Extremely low water and energy consumption
- Four compartment detergent box for manual dosing of powder or liquid detergent
- · High extraction force for efficient de-watering
- Door with gasket and strong hinges built for heavy duty operation
- Stainless and galvanized steel in all vital parts for high degree of rust protection
- Power Balance:
  - Maximizes the extraction force, leading to highest de-watering and savings in drying
  - Minimizes the stress on the machine, leading to trouble-free operation and increased machine lifetime
  - Reduces vibrations, making it possible to install the machine in all locations

## Main options

- · Stainless steel side panels
- · Voice guidance option



Coin, card ready, & OPL models available.

Images shown are a representation of the product only and variations may occur.

Main specifications				W5350X		
Max. capacity			35/77			
Drum,	volume diameter	,	litre/ft³ ø mm/inch		/12.4 36 1/4	
Extraction			rpm	- ·	50	
G-factor				<del>-</del> -	20	
Heating alterna	tives, 230/400V	electricity steam	kW	_	22 x	
		non-heated	t	:	x	
Consumption "Warm" *	data 6S03/6L33			Full load, 35 kg / 77 lb	Half load, 17.5 kg / 33.5 lb**	
Total time			min	30	28	
Water consump	otion (cold+hot)		litre/gallon	308/81.4+31/8.2	179/47.3+16/4.2	
Energy consumption (motor/heating/hot water) kWh				0.40/2.55/2.0	0.40/1.6/1.0	
Steam consum	ption		kg/lbs	6.8/15.0	3.9/8.6	
Residual moist	ure		%	-	-	
* Water temperature 59 ** Programs with AWS.	9°F cold water and 149°F hot water.					

Certified in accordance with ISO 9001 and ISO 14001 and approved IP 24D. Certified in accordance with UL/ETL standards.



Electrical connections							
Heating alternative	Main voltage	Hz	Heating power kW	Total power kW	Recommended ITCB A		
Electric heated	208-240V 3 ~	60	18.0-24.0	19.2-25.2	80		
Non heated or steam heated	208-240V 1 ~ 208-240V 3 ~	60 60	- -	2.3 1.8	15 15		

Water and steam connection		W5350X
Water valves Water pressure Capacity at 300 kPa Drain valve Steam valve Steam pressure	DN/inch psi I/min ø mm/inch DN/inch psi	20 / 3/4 30-90 60 75 / 3 15 / 1/2 7-40
Floor requirements		
Frequency of the dynamic force Floor load at max extraction	Hz kN	10.8 6.9 ± 10.7
Sound levels		
Sound power level (IEC 60704-2-4) wash extraction	dB(A) dB(A)	65 82
Heat emission		
% of installed power, max	5	
Shipping data		
Weight Shipping volume	net, kg/lbs crated, kg/lbs m³/ft³	560 / 1235 580 / 1279 2.7 / 291
Dimensions in mm/inch		
A Width B Depth C Height D E F G H I J K L M N		1085 / 42 11/16 1105 / 43 1/2 1570 / 61 13/16 530 / 20 7/8 120 / 4 3/4 525 / 20 11/16 55 / 2 3/16 1480 / 58 1/4 220 / 8 11/16 1445 / 56 7/8 315 / 12 3/8 415 / 16 5/16 120 / 4 3/4 190 / 7 1/2
2 Door opening ø 535 mm / 21 1/16 inch	6 Water re-use 7 Drain valve 8 Liquid detergen	

Electrical connection

10 Steam connection

Detergent box


Cold water


Hot water


3

4

5







Art. No. 438919532US/2013.05.10
We reserve the right to alter specifications without notice.

For Electrolux Professional Laundry Solutions in North America, please contact:

<sup>\*</sup> Other voltages available, see installation manual